



Technical Data Sheet

Everlast 50-400M

Valve Lubricant/Sealant W/Moly

Description:

50-400M is resistant to water, organic acids, dilute caustic solutions and hydrocarbons such as gasoline, jet fuel, lubricating oils and mixtures of these products. 50-400M is inhibited for use in H₂S and/or CO₂. Meets Mil-G-6032 "Grease Plug Valve, Gasoline & Oil Resistant." Contains Moly for EP protection. Available in winter grade to < -40 F.

Applications:

For use in plug, ball, and gate valves. Suitable for use in hydrocarbon gasses. DO NOT use in oxygen service

Features:

- Water insoluble and washout resistant
- Fully additive treated
- 100% synthetic
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H₂S and CO₂

Physical Properties:

- Color Silver/ Grey
- Temperature Range -20 to 450°F
- Consistency, Cone Penetration (D-217) 175 to 205
- Drop Point, °C None
- Thickener Inorganic

ADDRESS:

23609 West Hardy Road
Spring, TX 77373

PHONE:

(800) 929-0244

EMAIL:

sales@lubchem.com

FACEBOOK:

facebook.com/lubchem

LINKEDIN:

@lubchem-inc