



Technical Data Sheet

Longlife 1600M

Multi-Purpose Lubricant with Moly

Description:

Longlife 1600M is non-melting, water resistant and fully additive treated with corrosion inhibitors, extreme pressure additives and rust inhibitor additives. It is an excellent choice for lubrication of equipment in wet environments under highly loaded conditions. Available in NLGI Grade 0, 1, 2.

Applications:

Use on swivel joints, pumps and flanges. Suitable for use in the presence of hydrocarbon gasses. For use in plug, ball and gate valves.

Features:

- Outstanding performance
- Water insoluble and washout resistant
- Fully additive treated
- Non-melting multipurpose grease
- Superior protection to lubricate a wide variety of heavy-duty equipment
- Low Staining

Physical Properties:

- Color Light grey
- Temperature Range -75 to 350°F
- Consistency, Cone Penetration (D-217) 355 to 385 (NLGI 0)
- Consistency, Cone Penetration (D-217) 310 to 340 (NLGI 1)
- Consistency, Cone Penetration (D-217) 265 to 295 (NLGI 2)
- Drop Point, °C None
- Thickener Inorganic

ADDRESS:

23609 West Hardy Road
Spring, TX 77373

PHONE:

(800) 929-0244

EMAIL:

sales@lubchem.com

FACEBOOK:

facebook.com/lubchem

LINKEDIN:

@lubchem-inc