



## Technical Data Sheet

### Everlast 50-400DA

Frac and Production Valve Low Temperature Lubricant/Sealant

#### Description:

50-400DA is a low temperature valve lubricant/sealant resistant to acids, caustic solutions and is inhibited for use in H<sub>2</sub>S and/or CO<sub>2</sub>. 50-400DA has excellent dual resistance to water and aliphatic hydrocarbons such as gasoline, jet fuel, lubricating oils, organic condensates, and mixtures of these products. 50-400DA can be used in a wide variety of applications from the wellhead to product pipelines and frac valves.

#### Applications:

For use in plug, ball, and gate valves. Suitable for use in hydrocarbon gasses. DO NOT use in oxygen service

#### Features:

- Excellent low temperature pumpability
- Water insoluble and washout resistant
- Fully additive treated
- 100% synthetic
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H<sub>2</sub>S and CO<sub>2</sub>

#### Physical Properties:

- Color ..... Light Brown
- Temperature Range ..... -40 to 400°F
- Consistency, Cone Penetration (D-217) ..... 270 to 280
- Drop Point, °C ..... None
- Thickener ..... Inorganic

#### ADDRESS:

23609 West Hardy Road  
Spring, TX 77373

#### PHONE:

(800) 929-0244

#### EMAIL:

sales@lubchem.com

#### FACEBOOK:

facebook.com/lubchem

#### LINKEDIN:

@lubchem-inc