



## Technical Data Sheet

### Everlast 50-400

Valve Lubricant/Sealant

#### Description:

50-400 is resistant to water, organic acids, dilute caustic solutions and hydrocarbons such as gasoline, jet fuel, lubricating oils and mixtures of these products. 50-400 is inhibited for use in H<sub>2</sub>S and/or CO<sub>2</sub>. Meets Mil-G-6032 "Grease Plug Valve, Gasoline & Oil Resistant." Available in winter grade to < -40 F.

#### Applications:

For use in plug, ball, and gate valves. Suitable for use in hydrocarbon gasses. DO NOT use in oxygen service

#### Features:

- Water insoluble and washout resistant
- Fully additive treated
- 100% synthetic
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H<sub>2</sub>S and CO<sub>2</sub>

#### Physical Properties:

- Color ..... Light Brown
- Temperature Range..... -20 to 450°F
- Consistency, Cone Penetration (D-217) ..... 215 to 230
- Drop Point, °C..... None
- Thickener ..... Inorganic

#### ADDRESS:

23609 West Hardy Road  
Spring, TX 77373

#### PHONE:

(800) 929-0244

#### EMAIL:

sales@lubchem.com

#### FACEBOOK:

facebook.com/lubchem

#### LINKEDIN:

@lubchem-inc