



Technical Data Sheet

Everlast 50-400WG

Valve Lubricant/Sealant

Description:

50-400 WG is designed for use in plug valves as a sealant and in ball and gate valves as lubricant. 50-400 WG is resistant to acids, caustic solutions and is inhibited for use in H₂S and/or CO₂. This product has excellent dual resistance to water and aliphatic hydrocarbons such as gasoline, jet fuel, lubricating oils, organic condensates, and mixtures of these products. 50-400 WG can be used in a wide variety of applications from the wellhead to product pipelines.

Applications:

For use in plug, ball, and gate valves
Suitable for use in hydrocarbon gasses.
DO NOT use in oxygen service.

Features:

- Gasoline and Oil Resistant
- Water insoluble and washout resistant
- Fully additive treated
- 100 % synthetic
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H₂S and CO₂

Physical Properties:

- Color..... Amber
- Temperature Range -40 to 450°F
- Consistency, Cone Penetration (D-217)..... 260 to 280
- Drop Point, °C None
- Thickener Inorganic

ADDRESS:
23609 West Hardy Road
Spring, TX 77373

PHONE:
(800) 929-0244

EMAIL:
sales@lubchem.com

FACEBOOK:
facebook.com/lubchem

LINKEDIN:
@lubchem-inc