



## Technical Data Sheet

### Everlast 50-400 XP2

Frac And Production Valve Low Temperature Lubricant/Sealant

#### Description:

50-400 XP2 is a low temperature valve lubricant/sealant resistant to acids, caustic solutions and is inhibited for use in H<sub>2</sub>S and/or CO<sub>2</sub>. 50-400 XP2 has excellent dual resistance to water and aliphatic hydrocarbons such as gasoline, jet fuel, lubricating oils, organic condensates, and mixtures of these products. 50-400 XP2 can be used in a wide variety of applications from the wellhead to product pipelines and frac valves.

#### Applications:

For use in plug, ball, and gate valves.  
Suitable for use in hydrocarbon gasses.  
DO NOT use in oxygen service.

#### Features:

- Water insoluble and washout resistant
- Fully additive treated
- 100 % synthetic
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H<sub>2</sub>S and CO<sub>2</sub>
- Excellent low temperature pumpability

#### Physical Properties:

- Color ..... Light Brown
- Temperature Range ..... -40 to 400°F
- Consistency, Cone Penetration (D-217) ..... 270 to 280
- Drop Point, °C ..... None
- Thickener..... Inorganic

**ADDRESS:**  
23609 West Hardy Road  
Spring, TX 77373

**PHONE:**  
(800) 929-0244

**EMAIL:**  
sales@lubchem.com

**FACEBOOK:**  
facebook.com/lubchem

**LINKEDIN:**  
@lubchem-inc