



## Technical Data Sheet

### Everlast 50-400HV

High Viscosity Lubricant/Sealant Version of 50-400 (see 50-400 specs below).

#### Description:

50-400 is a dual-purpose valve lubricant/sealant that meets Mil-G6032 "Grease Plug Valve, Gasoline & Oil Resistant". 50-400 is resistant to acids, caustic solutions and is inhibited for use in H<sub>2</sub>S and/or CO<sub>2</sub>. This product has excellent dual resistance to water and aliphatic hydrocarbons such as gasoline, jet fuel, lubricating oils, organic condensates, and mixtures of these products.

#### Applications:

For use in plug, ball, and gate valves. Suitable for use in hydrocarbon gasses. DO NOT use in oxygen service

#### Features:

- Water insoluble and washout resistant
- Fully additive treated
- 100% synthetic
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H<sub>2</sub>S and CO<sub>2</sub>

#### Physical Properties:

- Color ..... Light Brown
- Temperature Range ..... -20 to 450°F
- Consistency, Cone Penetration (D-217) ..... 170 to 190
- Drop Point, °C ..... None
- Thickener ..... Inorganic

#### ADDRESS:

23609 West Hardy Road  
Spring, TX 77373

#### PHONE:

(800) 929-0244

#### EMAIL:

sales@lubchem.com

#### FACEBOOK:

facebook.com/lubchem

#### LINKEDIN:

@lubchem-inc