



## Technical Data Sheet

### Everlast 3 Arctic Grade

Low Temperature Valve Lubricant

#### Description:

Everlast 3 is a biodegradable synthetic lubricant resistant to hydrocarbon liquids and gases, including gasoline and kerosene, fuel and lubricating oils, natural gas and brine water. Everlast 3 is effective at intermittent temperatures to 550°F and is fortified with antirust, anti-wear, and corrosion inhibitors. The unique additive package in Everlast 3 bonds to metal surfaces reducing the damaging effects of corrosion and scale deposition on critical valve components.

#### Applications:

For use in plug, gate and ball valves Suitable for use in hydrocarbon gases DO NOT use in oxygen service

#### Features:

- 100% synthetic
- Water resistant
- Fully additive treated
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H<sub>2</sub>S

#### Physical Properties:

- Color ..... White
- Temperature Range ..... -70 to 550°F
- Consistency, Cone Penetration (D-217) ..... 230 to 250
- Drop Point, °C ..... None
- Thickener ..... Inorganic

**ADDRESS:**  
23609 West Hardy Road  
Spring, TX 77373

**PHONE:**  
(800) 929-0244

**EMAIL:**  
sales@lubchem.com

**FACEBOOK:**  
facebook.com/lubchem

**LINKEDIN:**  
@lubchem-inc