



Technical Data Sheet

Everlast 3 Winter Grade

Low Temperature Valve Lubricant

Description:

Everlast 3 is a biodegradable synthetic lubricant resistant to hydrocarbon liquids and gases, including gasoline and kerosene, fuel and lubricating oils, natural gas and brine water. Everlast 3 is effective at intermittent temperatures to 550°F and is fortified with antirust, anti-wear, and corrosion inhibitors. The unique additive package in Everlast 3 bonds to metal surfaces reducing the damaging effects of corrosion and scale deposition on critical valve components.

Applications:

For use in plug, gate and ball valves Suitable for use in hydrocarbon gases DO NOT use in oxygen service.

Features:

- 100% synthetic
- Water resistant
- Fully additive treated
- High metal adhesion
- Excellent corrosion resistance
- Inhibited for H₂S

Physical Properties:

- Color White
- Temperature Range-40 to 550°F
- Consistency, Cone Penetration (D-217) 230 to 250
- Drop Point, °C None
- Thickener Inorganic

ADDRESS:

23609 West Hardy Road
Spring, TX 77373

PHONE:

(800) 929-0244

EMAIL:

sales@lubchem.com

FACEBOOK:

facebook.com/lubchem

LINKEDIN:

@lubchem-inc