



Technical Data Sheet

Formasil CO2

Valve Sealant

Description:

Formasil CO2 is a dual-purpose valve lubricant/sealant that meets Mil-G-6032 "Grease Plug Valve, Gasoline & Oil Resistant". Formasil CO2 is designed for use in gate valves as a lubricant/sealant and in ball and plug valves as a sealant. Formasil CO2 is resistant to acids, caustic solutions and is inhibited for use in H2S and/or CO2. This product has excellent dual resistance to water and petroleum products such as gasoline, jet fuel, lubricating oils and mixtures of these products. Formasil CO2 can be used in a wide variety of applications from the wellhead to product pipelines.

Applications:

For use in plug, gate and ball valves. Suitable for use in hydrocarbon gases. DO NOT use in oxygen service.

Features:

- Meets Mil-G-6032 "Grease Plug Valve, Gasoline and Oil Resistant"
- Water insoluble and washout resistant
- 100 % synthetic
- Inhibited for H2S and CO2

Physical Properties:

- Temperature Range -20 to 400 F
- Consistency, Cone Penetration (D-217)170 - 200

ADDRESS:

23609 West Hardy Road
Spring, TX 77373

PHONE:

(800) 929-0244

EMAIL:

sales@lubchem.com

FACEBOOK:

facebook.com/lubchem

LINKEDIN: