



## Technical Data Sheet

### Valve Saver AW

Valve Cleaner/Lubricant

#### Description:

Valve Saver AW is designed to lubricate and clean deposits common to valves in pipeline operations. Valve Saver AW is a premium quality non-melting base grease blended with a dispersant / surfactant. This unique compound will lubricate the valves internal components and, at the same time, emulsify a variety of organic and organo-metallic compounds common to pipeline operations.

#### Applications:

Apply Lubchem Valve Saver with conventional lubricating equipment. Turn valve slowly and repeat the process until valve opens freely. After the valve is operable, lubricate with one of Lubchem's high quality valve lubricants.

#### Features:

- Compatible with all valve lubricants
- Cuts residual gum and lacquer deposits left by valve lubricants
- Removes rust and corrosion
- Eliminates costly shut down and valve removal
- Do not use in oxygen service

#### Physical Properties:

- Color ..... White
- Temperature Range .....-65 to 450°F
- Consistency, Cone Penetration (D-217) ..... 280 to 350
- Drop Point, °C ..... None
- Thickener ..... Inorganic

#### ADDRESS:

23609 West Hardy Road  
Spring, TX 77373

#### PHONE:

(800) 929-0244

#### EMAIL:

sales@lubchem.com

#### FACEBOOK:

facebook.com/lubchem

#### LINKEDIN:

@lubchem-inc