

MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373
Telephone (281) 350-9600

Section I - Product Identification

Product Name: Everlast No. 4 Product Type: Valve Lubricant

Section II - Hazardous Ingredients / Identity Information

Hazardous Components	Approx. %	OSHA PEL	EXPOSURE LIMITS, PPM		Recommended
			Other Limits ACGIH TLV		

This product contains NO hazardous ingredients according to OSHA 29 CFR 1910.1200.

Special Hazard Designations

			HMIS	NFPA
DOT (49 CFR172): Not regulated				
OSHA (29CFR1910.1200) Evaluation:	Non hazardous	Health:	1	1
RCRA (40CFR261) Evaluation: Non Hazardous		Flammability:	1	1
EPA/TSCA Listed Ingredients: None		Reactivity: 0	0	

Key: 0-minimal 1-Slight 2-Moderate 3-Serious 4-Severe

Section III - Health Hazard Data

Routes of Entry: Inhalation: No Skin: No Ingestion: No
Health Hazards (Chronic): None Known
Carcinogenicity: NTP: No IARC Monographs: No OSHA Regulated: No

Signs and Symptoms of Exposure:

Eyes: Mechanical irritant, prolonged exposure may cause irritation.
Inhalation: No effects known.
Ingestion: Moderately irritating by ingestion.
Skin: In contact with the skin product acts as slight local irritant and allergen.
Medical Conditions Generally Aggravated by Exposure: None known.

Section IV – Emergency and First Aid Procedures:

Emergency and First Aid Procedures:

Eyes: Flush eyes with water for 15 minutes while holding eyelids open. If irritation persists get medical attention.
Inhalation: First aid not anticipated to be needed
Ingestion: If large quantity is ingested get medical attention.
Skin: Wash thoroughly with soap and water, launder soiled clothing before reuse.

Section V - Fire and Explosion Hazard Data

Flash Point (method used): 555 F Flammable Limits-LEL: N/A UEL: N/A
Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical, Sand
Special Fire Fighting Procedures: Standard fireman's protection and self contained breathing apparatus. No other special firefighting procedures.
Unusual Fire and Explosion Hazards: None

Section VI – Accidental Release Measures:

Steps To Be Taken In Case Material Is Released Or Spilled: Attempt to recover. Pick up small spills with shovel or spatula.
Waste Disposal Method: Comply with all governmental regulations.

Section VII - Handling and Storage:

Precautions To Be Taken In Handling And Storage: Do not store containers in direct sunlight, keep containers away from excessive heat.
Other Precautions: N/D

Section VIII - Control Measures:

Respiratory Protection (Specify Type): None expected to be required
Ventilation - Local Exhaust: Acceptable Special: N/A
Mechanical (General): N/A Other: N/A
Protective Gloves: Neoprene Coated Gloves Eye Protection: Safety Glasses
Other Protective Clothing or Equipment: None
Work / Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area.

Section IX - Physical / Chemical Characteristics

Boiling Point: N/A	Specific Gravity (H2O = 1): .98
Vapor Pressure (mm Hg.): N/A	Melting Point: None
Vapor Density (Air =1): N/A	Evaporation Rate (Butyl Acetate =1): N/A
Solubility In Water: nil	Appearance / Odor: Brown / Slight odor

Everlast No. 4
Valve Lubricant

MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373
Telephone (281) 350-9600

Section X - Reactivity Data

Stability: Material is Stable

Incompatibility (materials to avoid): Strong oxidizing agents, inorganic acids.

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide, Heavy Smoke

Hazardous Polymerization: Will not occur

Section XI – Toxicological Information:

N/A

Section XII – Ecological Information:

Non-hazardous

Section XIII – Disposal Consideration:

According to State and Federal Regulation

Section XIV – Transport Information:

N/A Material is non-hazardous

Section XV – Regulatory Information:

N/A

Section XVI – Other:

This document is prepared pursuant to the OSHA Hazard Communication Standard (29CFR1910.1200). The information herein is given in good faith, but no warranty, express or implied, is made. Consult Lubchem, Inc. For further information: 281-350-9600.

Abbreviations: N/A: Not Applicable N/D: Not Determined

Everlast No. 4
Valve Lubricant