MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373 Telephone (281) 350-9600

Section I - Product Identification Product Name: Valve Saver AW Product Type: Valve Cleaner

Section II - Hazardous Ingredients / Identity Information

EXPOSURE LIMITS, PPM

Hazardous Approx. Other Limits

Components % OSHA PEL ACGIH TLV Recommended

Petroleum Hydrocarbon >75 5mg/m3 5mg/m3 STEL 10

CAS # 64742-52-5

SARA 313 - not applicable unless otherwise noted by an asterisk (*) next to an ingredient in section II which directs the reader to a footnote at the bottom of this section stating this item is listed on the SARA section 313 inventory.

Ingredients are proprietary. Potential hazards have been evaluated and pertinent information has been included in sections III and VII. Each proprietary material is either: Held a trade secret from Lubchem, OSHA non-hazardous or below 1% if OSHA hazardous, and below 0.1% if potentially carcinogenic.

* These items are listed on the SARA Title III section 313 inventory.

Special Hazard Designations

DOT (49 CFR172): not regulated

OSHA (29CFR1910.1200) Evaluation: Hazardous

EPA/TSCA Listed Ingredients:None

Health:

Flammability:

Reactivity:

0

Section III - Physical / Chemical Characteristics

Boiling Point F: 270-470 Vapor Density (Air =1): >1

Specific Gravity (H2O = 1): N/D Evaporation Rate (Butyl Acetate =1): <1

Vapor Pressure (mm Hg.): N/D Solubility In Water: negligible
Melting Point: N/D Appearance / Odor: Tan / Grease

Section IV - Fire and Explosion Hazard Data

Flash Point (method used): 263-515 Flammable Limits-LEL: N/D UEL: N/D

Extinguishing Media: Carbon Dioxide, Foam, Dry Chemical.

Section IV - Fire and Explosion Hazard Data cont.

Special Fire Fighting Procedures: Water stream may spread fire, use water spray to cool containers only. Unusual Fire and Explosion Hazards: Will not flash spontaneously. May ignite if exposed to open flame.

Section V - Reactivity Data

Stability: Material is stable

Conditions to Avoid: Avoid conditions that could generate an oil mist. Do not expose the product to strong oxidizers or excessive heat.

Incompatibility (materials to avoid): Strong oxidizers

Hazardous Decomposition Products: carbon smoke, oxides of carbon, various hydrocarbons can evolve other toxic gasses, vapors and solid residue.

Hazardous Polymerization: Will not occur.

Section VI - Health Hazard Data

Health Hazards (Chronic): None Known

Carcinogenity: NTP: No IARC Monographs: No OSHA Regulated: No

MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373 Telephone (281) 350-9600

Signs and Symptoms of Exposure:

Eyes: Under normal conditions of use, expected to cause no more than minor, if any eye irritation based on data from components.

Inhalation: Not expected to be acutely toxic by inhalation. Breathing petroleum oil mist at concentrations in air that exceed the recommended exposure standard can cause respiratory irritation and discomfort. Ingestion: May cause nausea, irritation, or diarrhea. Possible aspiration hazard.

Skin: Under normal conditions of use, no adverse health effects are expected upon short-term contact. Prolonged or repeated contact may produce skin irritation and inflammation. Primary hazard associated with grease in high-pressure gun, necrosis could result.

Medical Conditions Generally Aggravated by Exposure: None Known.

Emergency and First Aid Procedures:

Eyes: Flush eyes with water for 15 minutes while holding eyelids open. If irritation persists get medical attention.

Inhalation: If irritation occurs, move to fresh air. If breathing has stopped give artificial respiration and get medical attention immediately.

Ingestion: If ingested get medical attention, do not induce vomiting.

Skin: Wash thoroughly with soap and water, if injected under skin get immediate medical attention.

Launder soiled clothing before reuse.

Section VII - Precautions for Safe Handling and Use

Steps To Be Taken In Case Material Is Released or Spilled: Attempt to recover. Pick up small spills with shovel or spatula.

Waste Disposal Method: Comply with all governmental regulations.

Precautions To Be Taken In Handling And Storage: Do not store containers in direct sunlight, keep containers away from excessive heat.

Other Precautions: N/D

Section VIII - Control Measures:

Respiratory Protection (Specify Type): None expected to be required Ventilation - Local Exhaust: Acceptable Special: N/A Mechanical (General): N/A Other: N/A

Other Protective Clothing or Equipment: None

Work / Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area.

Section IX - Physical / Chemical Characteristics

Boiling Point F: 270-470 Vapor Density (Air =1): >1

Specific Gravity (H2O = 1): N/D Evaporation Rate (Butyl Acetate =1): <1

Vapor Pressure (mm Hq.): N/D Solubility In Water: negligible

Melting Point: N/D Appearance / Odor: Black / Lubricant

Section X - Reactivity Data

Stability: Material is stable

Conditions to Avoid: Avoid conditions that could generate an oil mist. Do not expose the product to strong oxidizers or excessive heat.

Incompatibility (materials to avoid): Strong oxidizers

Hazardous Decomposition Products: carbon smoke, oxides of carbon, various hydrocarbons can evolve other toxic gasses, vapors and solid residue.

Hazardous Polymerization: Will not occur.

MATERIAL SAFETY DATA SHEET

Lubchem, Inc. 23609 W. Hardy Rd. Spring, TX 77373 Telephone (281) 350-9600

Section XI - Toxicological Information:

NA

Section XII - Ecological Information:

Non-hazardous

Section XIII - Disposal Consideration:

Disposal should be in accordance with Federal and State regulations

Section XIV - Transport Information:

NA Material is non-hazardous/non-regulated

Section XV - Regulatory Information:

NA

Section XVI - Other:

None

This document is prepared pursuant to the OSHA Hazard Communication Standard (29CFR1910.1200). The information herein is given in good faith, but no warranty, express or implied, is made. Consult Lubchem, Inc. For further information: 281-350-9600.

Abbreviations: N/A: Not Applicable N/D: Not Determined